



Equipment for Applying Rejuvaseal

The DESCO D200 Distributor is a machine designed specifically for applying asphalt rejuvenator / sealer material. It is a precision spraying machine that will apply material to large areas of asphalt, paving quickly, precisely and economically.

Fully enclosed spray bar covers 8 foot wide swath with each pass. The spray bar manifold is split with six spray tips on the left side and four spray tips on the right side. Spray bar control is interlocked to permit spraying when the spray bar is in the □down□position only.

Machine can apply material at a rate of 0.04 to 0.08 gallons per square yard. Application ground speed is from 85 to 150 yards per minute. Control panel has a ground speed control that can be preset to the desired application speed. This control is actuated when the foot pedal is fully depressed in the forward direction. A digital meter on the control panel monitors ground speed.



SPECIFICATIONS:

Material Tank:	200-Gallon Material Tank with a Sealed Hatch
Material Pump:	Variable Speed to Accurately Meter Material Flow Rate From 5 GPM to 18 GPM. A Digital Meter on the Control Panel Monitors the Flow Rate.
Engine:	27 H.P. Air-Cooled Engine Driving a Hydro-Transmission Pump and a Constant Pressure Auxiliary Hydraulic Pump. 8 MPH is the Maximum Ground Speed.
Dimensions:	141" L x 95" W x 64" H
Approx. Weight:	2200 lbs.